

## Engineering Product Specification

### F1206- Series

The information contained in this document is the property of SINOCHIP Tech. Ltd. It is not for public disclosure. Possession of the information does not convey any right to loan, sell or disclose the CONFIDENTIAL information. Unauthorized reproduction or use of the information is prohibited. This document is to be returned to SINOCHIP Tech. LTD. Upon completion of the purposes for which it is loaned

Rev. #	Revision Description	Date	Author	Appr.
A	Original	3/26'07	SEA	C. X. M.
B	Add Application; Update UL No.; Correct Interrupting Rating.	8/22'08	Jesse	SEA
C	Add Halogen-free; Update Interrupting Rating from 35A to 50A; Add p/n "F1206-6.0A" .	9/25'08	Jesse	SEA
D	Update Item 2、Item 9.	11/5'08	Jesse	SEA
E	Update IT curve & $I^2t$ curve.	11/25'08	Jesse	SEA
F	Update Cold Resistance & Electrical Characteristics	1/06'09	Jesse	Alan
G	Update Cold Resistance & Electrical Characteristics	7/15'09	Rock	Alan

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 2 of 13</b>

## Table of Contents

<b>Section</b>	<b>Title</b>	<b>Page</b>
<b>1.</b>	<b>Scope</b>	<b>3</b>
<b>2.</b>	<b>General</b>	<b>3</b>
<b>3.</b>	<b>Manufacturer and Production Facility</b>	<b>3</b>
<b>4.</b>	<b>Agency / Certificate Information</b>	<b>3</b>
<b>5.</b>	<b>Catalog Symbol</b>	<b>4</b>
<b>6.</b>	<b>Ordering Information</b>	<b>4</b>
<b>7.</b>	<b>Shape &amp; Dimensions</b>	<b>5</b>
<b>8.</b>	<b>Recommended Land Patterns</b>	<b>6</b>
<b>9.</b>	<b>Materials</b>	<b>6</b>
<b>10.</b>	<b>Time Current Curve</b>	<b>6</b>
<b>11.</b>	<b>I<sup>2</sup>T vs Time Curve</b>	<b>8</b>
<b>12.</b>	<b>Temperature Derating Curve</b>	<b>9</b>
<b>13.</b>	<b>Reliability Test</b>	<b>10</b>
<b>14.</b>	<b>Recommended Solder Curve</b>	<b>11</b>
<b>15.</b>	<b>Packaging</b>	<b>12</b>
<b>16.</b>	<b>Storage</b>	<b>13</b>
<b>17.</b>	<b>Application</b>	<b>13</b>

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 3 of 13</b>

## 1. Scope

This Specification applies to F1206 series SMD fuses.

## 2. General

- Fast acting
- RoHS compliant
- Halogen-free
- 3.1mm×1.55mm physical size
- Thick film manufacturing method, ceramic substrate, silver fusing element
- Higher temperature profiles
- Excellent environmental integrity

## 3. Manufacturer and Production Facility

- Manufacturer  
Nanjing Sinochip Technology & development Co.,  
Ltd. Qingma Road 6#  
Maqun Science & Technology Park  
Nanjing City, Jiangsu Province, P. R. China  
Phone: 086-25-52153380  
Fax: 086-25-52157065

## 4. Agency / Certificate Information

- UL Recognition Card:  
JDYX2.E319540, JDYX8.E319540
- ISO 9001:2000, Certificate Number 10807Q10334ROS

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 4 of 13</b>

## 5. Catalog Symbol

Example F1206-1.0A

### **F 1206- 1.0A**

① ② ③

- ①. Symbol of Sinochip Electrical Characteristic: F = Fast acting
- ②. Size Number
- ③. Ampere Rating: 1A

## 6. Ordering Information

Part Number	Mark	Current Rating (A)	Voltage Rating (V)	Interrupting Rating 32V DC	Typical Cold DCR* (Ω)	Nominal I <sup>2</sup> T** (A <sup>2</sup> S)
F1206-0.5A	F	0.50	32	50A	1.375	0.0155
F1206-0.75A	G	0.75	32	50A	0.605	0.0267
F1206-1.0A	H	1.00	32	50A	0.270	0.0279
F1206-1.5A	K	1.50	32	50A	0.130	0.0491
F1206-2.0A	N	2.00	32	50A	0.074	0.1251
F1206-2.5A	O	2.50	32	50A	0.051	0.1255
F1206-3.0A	P	3.00	32	50A	0.033	0.1350
F1206-3.15A	R	3.15	32	50A	0.030	0.1490
F1206-3.5A	R	3.50	32	50A	0.0325	0.1948
F1206-4.0A	S	4.00	32	35A	0.021	0.3025
F1206-5.0A	T	5.00	32	35A	0.0165	0.5207
F1206-6.0A	6	6.00	32	35A	0.0145	0.8134
F1206-7.0A	U	7.00	32	35A	0.0085	4.0418

\* Measured at ≤10% rated current and 25℃.

\*\* Melting I<sup>2</sup>T at 10 times of rated current.

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



Title: Engineering Product Specification F1206 Series

Revision: G

Printed on: 7/15'09

Page 5 of 13

## 7. Shape & Dimensions: (mm)




L	W	T	B
3.10±0.20	1.55±0.20	0.55±0.20	0.40±0.10

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Title: Engineering Product Specification F1206 Series	Revision: G
Printed on: 7/15'09	Page 6 of 13

## 8. Recommended Land Patterns: (mm)



A	B	C	D
2.1±0.3	4.7±0.5	1.5±0.3	1.5±0.3

## 9. Materials:


	Components	Material
1	Substrate	Ceramic
2	Terminations	Silver over-plated with tin (100%)
3	Element	Silver or Silver/palladium

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Title: Engineering Product Specification F1206 Series	Revision: G
Printed on: 7/15'09	Page 7 of 13

10. Time Current Curve:


Electrical Characteristics		
Ampere Rating	% of Current Rating	Opening Time
500mA-7A	100%	4 Hours Min.
500mA-7A	200%	60 Seconds Max.
500mA-7A	250%	5 Seconds Max.



This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Title: Engineering Product Specification F1206 Series	Revision: G
Printed on: 7/15'09	Page 8 of 13

## 11. $I^2T$ vs Time Curve:



This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



Title: Engineering Product Specification F1206 Series	Revision: G
Printed on: 7/15'09	Page 9 of 13


## 12. Temperature Derating Curve: (Ambient temperature on current-carrying capacity)

- For Circuit,current rating shall be derated in accordance with the figure.
- This current derating curve is for fusing characteristics.

Example,

Work Temp:80℃, Temp derating factor = 90%

$$\text{Melting } I^2 t_{\text{fuse}} \geq I^2 t_{\text{pulse}} / F_p / 0.9$$



This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 10 of 13</b>

## 13. Reliability Test:

Characteristics	Test condition / Methods	Requirement	Test Reference
Carrying capacity	100% of its rated current	No Fusing, 4hr min	Refer to SINOCHIP File
Fusing Time	200% of its rated current	Within 60sec	Refer to SINOCHIP File
	250% of its rated current	Within 5sec	Refer to SINOCHIP File
Solderability	235°C±5 °C, 3s±0.5s	95% coverage min	IEC60127/A.3.3; IEC60068-2-20; MIL-STD-202 Method 208H
Resistance to soldering	260°C±5 °C, 10s±0.5s	△R:<10%	MIL-STD-202 Method 210
Bending test	Distance between holding points: 90mm, Bending: 1mm, 1time, 10sec	(1) No mechanical damages (2) △R: <10%	Refer to SINOCHIP File
High Temperature Operating Life	96hours, 125°C at 60% rated current. Measure cold resistance and Time-Current characteristics.	(1)△R: <10%; (2)100% of Rating Current, Opening time >4 hours (3)200% of Rating Current, Opening time <60 seconds	MIL-STD-202 Method 108
Moisture Resistance	10 Cycles. Measure cold resistance and Time-Current characteristics.	(1)△R: <10%; (2)100% of Rating Current, Opening time >4 hours (3)200% of Rating Current, Opening time <60 seconds	MIL-STD-202 Method 106
High Temperature Exposure	1000 hrs. @ T=125°C. Unpowered. Measure cold resistance. and Time-Current characteristics.	(1)△R: <10%; (2)100% of Rating Current, Opening time >4 hours (3)200% of Rating Current, Opening time <60 seconds	MIL-STD-202 Method 108
Insulation Resistance	DC resistance	0.1MΩ min	IEC60127-4
ON /OFF Cycle Test	Surge current and 100% rated current; 50s ON; 10s OFF; 100,000 Cycles	(1)No open; (2)100% of Rating Current, Opening time >4 hours (3)200% of Rating Current, Opening time <60 seconds	Refer to SINOCHIP File

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SINOCHIP Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SINOCHIP Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 11 of 13</b>

Salt spray	5% salt solution, 48 hours exposure	$\Delta R: <10\%$	MIL-STD-202 Method 101
Thermal Shock	10 cycles between $-55^{\circ}\text{C}/+125^{\circ}\text{C}$ , 30 minutes @each extreme	No mechanical damage; $\Delta R: <10\%$	IEC 60068-2-14
Interrupting Ability	Loading current 50A	without permanent arcing,ignition and bursting of fuse link	UL248-14


## 14. Recommended Solder Curve:

### 14.1 Infrared Reflow

14.1.1 Temperature:260°C

14.1.2 Time:30 Seconds Maximum

14.1.3 Recommend Reflow profile



Profile Feature	Pb-Free Assembly
Average Ramp-Up Rate(Ts <sub>max</sub> to Tp)	3°C/second max.
Preheat Temperature	150°C
Min(Ts <sub>min</sub> ) Temperature	200°C
Max(Ts <sub>max</sub> ) Time(Ts <sub>min</sub> to Ts <sub>max</sub> )	60-120 seconds
Peak Temperature(Tp)	260°C
Time within 5°C of actual Peak Temperature(Tp)	20-40 seconds
Ramp-Down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SINOCHIP Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SINOCHIP Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible

<b>Title: Engineering Product Specification F1206 Series</b>	<b>Revision: G</b>
<b>Printed on: 7/15'09</b>	<b>Page 12 of 13</b>

## 14.2 Wave soldering

14.2.1 Reservoir Temperature:260℃

14.2.2 Time in Reservoir:10 Seconds Maximum


## 14.3 Hand Soldering

14.3.1 Temperature:380℃

14.3.2 Time:5 Seconds Maximum

## 15. Packaging:


- 5,000 pieces of fuses in paper taper and reeled on a 178mm(7 inch) reel.



Type	A	B	W	F	E
F1206	3.50 ±0.20	1.90 ±0.20	8.00 ±0.20	3.50 ±0.05	1.75 ±0.10
Type	P	P0	P1	D0	T
F1206	4.00 ±0.10	4.00 ±0.10	2.00 ±0.05	1.50 ±0.10	0.75 ±0.10

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SINOCHIP Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SINOCHIP Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible

Title: Engineering Product Specification F1206 Series	Revision: G
Printed on: 7/15'09	Page 13 of 13



Type	M	W	T	A	B	C	D
F1206	178 ±2.0	10.0 ±1.5	12.0 ±2.0	2.5 ±0.5	13.0 ±0.5	31.0 ±1.0	80.0 ±1.0

#### 16. Storage:

- The maximum ambient temperature shall not exceed 40℃.Storage temperature higher than 40℃ could result in the deformation of packaging materials.
- The maximum relative humidity recommended for storage is 65%.High humidity with high temperature can accelerate the oxidation of the solder plating on the termination and reduce the solderability of the components.
- Sealed plastic bags with desiccant shall be used to reduce the oxidation of the termination and shall only be opened prior to use. The products shall not be stored in areas where harmful gases containing sulfur or chlorine are present.

#### 17. Application:

- Battery pack
- PC related equipment and peripherals(Hard drive,Printer,etc.)
- Portable devices(Mobile phone,PDA battery charger,etc.)
- Digital camera(Digital still camera)
- Game equipment
- LCD monitor,LCD modules
- Wireless basestation

**END**

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. SART Tech. LTD. reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. SART Tech. LTD. also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.